



- 1 - Flexible conductor made of bare copper
- 2 - Silicone rubber insulation
- 3 - Silicone rubber sheath

TECHNICAL DATA

- Working temperature of the insulating materials – 60°C + 180°C
- Temperature over short period 230°C
- Resistance to flame not propagate the flame, self-extinguishing
- Impermeability excellent resistance to water
- Bending radius 3 x outer diameter
- Colouring of cable grey
- Colouring of conductors see table below
- Packaging coils or reels

Colouring of cables in accordance with UNI 7937 rules	Colouring of cable with 2 conductors	one conductor red and the other one white
	Colouring of cable with 3 conductors	two conductors red and the other one white
	Colouring of cable with 4 conductors	two conductors red and the others two white

Nominal size mm ²	Stranding n° wires x diam. mm	Outer diameter mm	Tolerance mm
2 x 0.25	8 x 0.20	4.60	± 0.10
2 x 0.35	11 x 0.20	4.80	
2 x 0.50	16 x 0.20	4.90	
3 x 0.25	8 x 0.20	4.70	
3 x 0.35	11 x 0.20	4.90	
3 x 0.50	16 x 0.20	5.10	
4 x 0.25	8 x 0.20	5.00	
4 x 0.35	11 x 0.20	5.20	
4 x 0.50	16 x 0.20	5.40	