



- 1 - Flexible conductor
- 2 - Silicone rubber insulation
- 3 - Silicone rubber sheath
- 4 - Galvanised steel wires or tin plated copper braid

TECHNICAL DATA

- Working temperature of the insulating materials - 60°C + 180°C
- Temperature over short period 230°C
- Resistance to flame not propagate the flame, self-extinguishing
- Alloys temperature range and technical data see Technical Data Alloys
- Impermeability excellent resistance to water
- Colouring of cable according to the standards DIN43714 ANSI MC96.1 IEC 584-3
- Bending radius 6 x outer diameter
- Packaging coils or reels

OPTIONS

- On request for minimum quantities of 500 m you can have braided stainless steel 304

Nominal size mm ²	Stranding n° wires x diam.mm	Galvanised steelwire outer diameter mm	Diameter tolerance mm	Tin plated copper outer diameter mm	Diameter tolerance mm	Type
2 x 0.25	8 x 0.20	5.90	± 0.30	5.50	± 0.20	Jx Kx Wx Tx Sx Rx Bx Bx ²
2 x 0.35	11 x 0.20	7.00		6.60		
2 x 0.50	6 x 0.32	7.20		6.80		
2 x 0.80	10 x 0.32	7.80		7.40		
2 x 1	12 x 0.32	8.00		7.60		
2 x 1.30	16 x 0.32	8.70		8.30		
2 x 1.50	19 x 0.32	8.80		8.40		