



- 1 - Flexible conductor made of bare copper or tin plated copper
- 2 - Silicone rubber insulation
- 3 - Silicone rubber sheath

TECHNICAL DATA

- Working temperature of the insulating materials - 60°C + 180°C
- Temperature over short period 230°C
- Rated voltage 300/500V
- Voltage testing 2000V/20mA
- Resistance to flame not propagate the flame, self-extinguishing
- Impermeability excellent resistance to water
- Colouring of cable red brick
- Colouring of conductors see table below
- Bending radius 4 x outer diameter
- Packaging coils or reels

Colouring of stranded cables according to standard HD 308 S2 DIN VDE 0293-308

With yellow/green	Without yellow/green
3 conductors: yellow green - brown - blue 4 conductors: yellow green - black - grey - brown 5 conductors: yellow green - black - blue - brown - grey	2 conductors: brown - blue 3 conductors: grey - black - brown 4 conductors: grey - black - brown - blue 5 conductors: grey - black - brown - blue - black
6 conductors or more: black with printed numbering starting from the inside+one yellow-green in the outside position	

Nominal size mm ²	Outer diameter mm	Nominal size mm ²	Outer diameter mm	Nominal size mm ²	Outer diameter mm	Nominal size mm ²	Outer diameter mm
2 x 0.50	5.60 ± 0.20	3 x 0.50	5.90 ± 0.20	4 x 0.50	6.50 ± 0.20	5 x 0.50	7.30 ± 0.20
2 x 0.75	6.40 ± 0.20	3 x 0.75	6.80 ± 0.20	4 x 0.75	7.60 ± 0.20	5 x 0.75	8.50 ± 0.20
2 x 1	6.60 ± 0.20	3 x 1	7.00 ± 0.20	4 x 1	7.90 ± 0.20	5 x 1	8.80 ± 0.20
2 x 1.50	7.60 ± 0.20	3 x 1.50	8.00 ± 0.20	4 x 1.50	8.80 ± 0.20	5 x 1.50	9.60 ± 0.20
2 x 2.50	8.80 ± 0.20	3 x 2.50	9.70 ± 0.20	4 x 2.50	10.60 ± 0.30	5 x 2.50	11.60 ± 0.30
2 x 4	10.80 ± 0.30	3 x 4	11.50 ± 0.30	4 x 4	12.60 ± 0.30	5 x 4	14.00 ± 0.30
2 x 6	12.40 ± 0.30	3 x 6	13.20 ± 0.30	4 x 6	14.60 ± 0.30	5 x 6	16.60 ± 0.40
-----	-----	3 x 10	17.30 ± 0.40	4 x 10	19.40 ± 0.40	-----	-----
-----	-----	3 x 16	19.40 ± 0.40	4 x 16	21.40 ± 0.40	-----	-----

Nominal size mm ²	Outer diameter mm	Nominal size mm ²	Outer diameter mm	Nominal size mm ²	Outer diameter mm	Nominal size mm ²	Outer diameter mm
6 x 0.50	8.30 ± 0.20	7 x 0.50	8.3 ± 0.20	12 x 1	12.60 ± 0.30	10 x 1.50	13.00 ± 0.40
6 x 0.75	9.20 ± 0.20	7 x 0.75	9.20 ± 0.20	12 x 1.50	14.00 ± 0.30	16 x 1.50	16.20 ± 0.40
6 x 1	9.50 ± 0.20	7 x 1	9.50 ± 0.20	12 x 2.50	17.10 ± 0.40	24 x 1	17.50 ± 0.40
6 x 1.50	10.40 ± 0.30	7 x 1.50	10.40 ± 0.30	-----	-----	24 x 1.50	19.80 ± 0.40
6 x 2.50	12.60 ± 0.30	7 x 2.50	12.60 ± 0.30	-----	-----	-----	-----