



- 1 - Flexible conductor
- 2 - Kapton tape
- 3 - Coloured P.T.F.E. tape
- 4 - Kapton tape

TECHNICAL DATA

- Working temperature of the insulating materials – 100°C + 350°C
- Temperature over short period 380°C
- Alloys temperature range and technical data see Technical Data Alloys
- Resistance to flame not propagate the flame, self-extinguishing
- Impermeability excellent resistance to water
- Colouring of cable brown
- Colouring of conductors according to the standards DIN43714 ANSI MC96.1 IEC 584-3
- Bending radius 5 x outer diameter
- Packaging coils or reels

OPTIONS

On request for minimum quantities you can have:

- Rigid conductor 300 m
- Twisted cable 300 m
- Different construction of stranding with single wire Ø 0.20 - 0.30 - 0.40 mm 3000 m

Nominal size mm ²	Stranding n° wires x diam. mm	Outer diameter mm	Type
2 x 0.22	7 x 0.20	1.25 x 2.16 ± 0.15	Jx Kx
2 x 0.35	11 x 0.20	1.50 x 2.60 ± 0.15	
2 x 0.50	6 x 0.32	1.65 x 2.90 ± 0.15	
2 x 0.80	10 x 0.32	1.95 x 3.50 ± 0.15	
2 x 1	12 x 0.32	2.00 x 3.70 ± 0.15	