


- 1 – Flexible conductor made of bare copper - nickel plated copper – nickel
- 2 – P.T.F.E. tape
- 3 – Fiberglass spiral impregnated with silicone rubber
- 4 – Fiberglass spiral impregnated with silicone rubber
- 5 – Fiberglass braid impregnated with silicone rubber

Sizes

1.50	3
1.75	4
2	6
2.50	



- 1 – Flexible conductor made of bare copper - nickel plated copper – nickel
- 2 – Fiberglass braid
- 3 – P.T.F.E. tape
- 4 – Fiberglass spiral impregnated with silicone rubber
- 5 – Fiberglass braid impregnated with silicone rubber

Sizes

8	16
10	25

TECHNICAL DATA

- Working temperature of the insulating materials – 60°C + 250°C
- Temperature over short period 280°C
- Rated voltage 300/500V
- Voltage testing 2000V/20mA
- Maximum temperature of bare copper conductor 200°C
- Maximum temperature of nickel plated copper conductor 350°C
- Maximum temperature of nickel 99,20% conductor 600°C
- Type of nickel plated copper 130 µm
- Resistance to flame not propagate the flame, self-extinguishing
- Colouring of cable with conductor made of bare copper white with black stripes
- Colouring of cable with conductor made of nickel plated copper white with blue stripes
- Colouring of cable with conductor made of nickel white with green stripes
- Bending radius 5 x outer diameter
- Packaging coils or reels

OPTIONS

On request for minimum quantities you can have:

- Different coloured stripes 500 m
- Different construction of stranding with single wire Ø 0.20 - 0.30 - 0.40 mm 3000 m

Nominal size mm ²	Stranding n° wires x diam. mm			Diameter	
	Bare copper mm	Nickel plated copper mm	Nickel mm	Outer mm	Tolerance mm
1.50	30 x 0.25	30 x 0.25	21 x 0.30	2.80	± 0.20
1.75	not provided	not provided	25 x 0.30	3.00	
2	not provided	28 x 0.30	28 x 0.30	3.10	
2.50	50 x 0.25	50 x 0.25	20 x 0.40	3.20	
3	not provided	24 x 0.40	24 x 0.40	3.90	
4	56 x 0.30	56 x 0.30	32 x 0.40	4.40	± 0.30
6	84 x 0.30	84 x 0.30	48 x 0.40	5.00	
8	not provided	64 x 0.40	64 x 0.40	6.00	
10	80 x 0.40	80 x 0.40	80 x 0.40	6.50	± 0.40
16	126 x 0.40	126 x 0.40	126 x 0.40	8.10	
25	196 x 0.40	196 x 0.40	196 x 0.40	9.00	