
	<p>1 - Flexible conductor made of nickel plated copper or nickel 2 - P.T.F.E. tape 3 - Fiberglass spiral impregnated with P.T.F.E. 4 - Fiberglass spiral impregnated with P.T.F.E. 5 - Fiberglass braid impregnated with P.T.F.E.</p>	<p>Sizes</p> <table border="1"> <tr><td>0.35</td><td>1.30</td><td>3.30</td></tr> <tr><td>0.50</td><td>1.50</td><td>4</td></tr> <tr><td>0.75</td><td>2</td><td>6</td></tr> <tr><td>0.82</td><td>2.50</td><td></td></tr> <tr><td>1</td><td>3</td><td></td></tr> </table>	0.35	1.30	3.30	0.50	1.50	4	0.75	2	6	0.82	2.50		1	3	
0.35	1.30	3.30															
0.50	1.50	4															
0.75	2	6															
0.82	2.50																
1	3																
	<p>1 - Flexible conductor made of nickel plated copper or nickel 2 - Fiberglass braid 3 - P.T.F.E. tape 4 - Fiberglass spiral impregnated with P.T.F.E. 5 - Fiberglass braid impregnated with P.T.F.E.</p>	<p>Sizes</p> <table border="1"> <tr><td>8</td><td>16</td></tr> <tr><td>10</td><td>25</td></tr> </table>	8	16	10	25											
8	16																
10	25																

TECHNICAL DATA

- Working temperature of the insulating materials - 60°C + 320°C
- Temperature over short period 350°C
- Rated voltage 500/750 V
- Voltage testing 3000V/20mA
- Maximum temperature of nickel plated conductor 350°C
- Maximum temperature of nickel 99,20% conductor 600°C
- Type of nickel plated copper 130 µm
- Resistance to flame not propagate the flame, self-extinguishing
- Colouring of cable brown
- Bending radius 5 x outer diameter
- Packaging coils or reels

OPTIONS

On request for minimum quantities you can have:

- Black stripes on brown wire 500 m
- Different construction of stranding with single wire Ø 0.20 - 0.30 - 0.40 mm 3000 m

Nominal size mm ²	Stranding n° wires x diam. mm		Diameter	
	Nickel plated copper	Nickel	Outer mm	Tolerance mm
0.35	5 x 0.30	11 x 0.20	2.10	± 0.20
0.50	7 x 0.30	16 x 0.20	2.15	
0.75	15 x 0.25	24 x 0.20	2.30	
0.82	not provided	26 x 0.20	2.40	
1	20 x 0.25	32 x 0.20	2.40	
1.30	19 x 0.30	19 x 0.30	2.60	
1.50	30 x 0.25	21 x 0.30	2.70	
2	28 x 0.30	28 x 0.30	3.00	
2.50	50 x 0.25	20 x 0.40	3.20	
3	24 x 0.40	24 x 0.40	3.90	
3.30	not provided	27 x 0.40	4.00	
4	56 x 0.30	32 x 0.40	4.40	± 0.30
6	84 x 0.30	48 x 0.40	5.00	
8	64 x 0.40	64 x 0.40	6.00	
10	80 x 0.40	80 x 0.40	6.30	± 0.40
16	126 x 0.40	126 x 0.40	8.10	
25	196 x 0.40	196 x 0.40	9.00	