



- 1 - Flexible conductor
- 2 - Fiberglass spiral impregnated with silicone rubber
- 3 - Fiberglass braid impregnated with silicone rubber
- 4 - Oval type: fiberglass braid
Round type: fiberglass braid impregnated with silicone rubber
- 5 - Tin plated copper braid

TECHNICAL DATA

- Working temperature of the insulating materials - 25°C + 250°C
- Temperature over short period 280°C
- Alloys temperature range and technical data see Technical Data Alloys
- Resistance to flame not propagate the flame, self-extinguishing
- Impermeability do not use in wet environments
- Colouring of cable according to the standards DIN43714 ANSI MC96.1 IEC 584-3
- Bending radius 6 x outer diameter
- The impregnation with silicone rubber of the fiberglass braid makes the braid soft and mechanically flexible
- Colouring of conductors white with coloured stripes
- Packaging coils or reels

OPTIONS

On request for minimum quantities you can have:

- Different construction of stranding with single wire Ø 0.20 3000 m
- Braided stainless steel 500 m

Nominal size mm ²	Stranding n° wires x diam.mm	Outer diameter			Type
		Round type mm	Oval type mm	Tolerance mm	
2 x 1.30	16 x 0.32	5.10	5.00 x 3.50	± 0.20	Jx Kx Wx Tx Sx Rx Bx Bx ²
2 x 1.50	19 x 0.32	5.60	5.50 x 3.60		